

## DALIS DCH otopné těleso 600x1154mm, 398W, chrom

Objednací kód: DCH-612

### Parametry


Barva: Chrom  
Materiál: Ocel  
Záruka: 2 roky



## Technický list

| Type    | Width<br>[mm] | Height<br>[mm] | Depth<br>[mm] | Connections spacing<br>[mm] | Connections distance<br>from the wall<br>[mm] | Brackets spacing<br>[mm] | Heating<br>surface<br>[m <sup>2</sup> ] | Weight<br>[kg] | Capacity<br>[dm <sup>3</sup> ] | Power (75/65/20 °C)<br>[W] | Power (75/65/24 °C)<br>[W] | Power (55/52/24 °C)<br>[W] | Electric heater<br>maximal power<br>[W] |
|---------|---------------|----------------|---------------|-----------------------------|-----------------------------------------------|--------------------------|-----------------------------------------|----------------|--------------------------------|----------------------------|----------------------------|----------------------------|-----------------------------------------|
| DCH-612 | 600           | 1154           | 104-124       | 550                         | 45-65                                         | 400                      | 1,16                                    | 11,7           | 5,9                            | 398                        | 358                        | 174                        | 300                                     |

Horizontal tubes: 

Vertical manifolds: 

|                       |                                                                         |
|-----------------------|-------------------------------------------------------------------------|
| Finish and guarantee: | galvanic chrome – 5 year guarantee                                      |
| Mounting brackets:    | set for assembly on the wall;<br>brackets in the colour of a towel rail |
| Valve:                | for a separate order – page 25                                          |
| Heater:               | for a separate order – page 24                                          |
| Accessories:          | for a separate order – page 26                                          |
| Working pressure:     | 10 bars                                                                 |
| Maximal temperature:  | 95 °C                                                                   |

|              |                                                                                                                                                    |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Connections: |  – inner threads G 1/2<br>– air-vent plug G1/8<br>hidden behind |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------|

