


LEMURIAN 60x120 / 120x120




Properties

Size	60x120 / 120x120
Shape	Square, Rectangle
Surface	Polished
Colours	Other colors, Multicolored
Texture	Marble
Character	Rectified, Porcelain, Frost resistance
Category	Wall tiles, Floor tiles, Stone & Concrete




PEI
II



LEM001 60x120 cm
Thickness 9
Package contains 1.44 m², 2

PEI
II



LEM002 120x120 cm
Thickness 9
Package contains 1.44 m², 1

Explanations

PU

Polished surface

Polished tinted shade of unglazed tile.

RT

Rectified tiles

Rectified tiles are also known as dimensionally stable tiles. These are tiles that have been mechanically trimmed to a certain size after they have been fired so that their edges are 90°. Achieved uniform size, consistency and optimum precision give the tile a cleaner finish and fewer deviations between tiles. Rektifizierte Fliesen sind für Verlegung mit einer Mindestfuge von 2 mm geeignet.

PO

Porcelain tiles

By pushing into the mold under high pressure remains in the ceramics minimum of air bubbles. It is then fired at high temperatures, making the final product hard, strong and abrasion resistant. At the same time, it is less absorbent. Located universal use in interior and exterior, on walls and floors. Sintered paving is especially suited to high-stressed areas such as tiles or building facades.



Frost resistance

Frost resistance is determined by the degree of water absorption of the tile (ie it does not provide water to freeze it). For tiles for indoor use is not required frost resistance and moisture absorption is usually more than 10 %. In contrast, frost-resistant glazed tiles have an absorption of up to 3 %. For exterior are suitable sintered tiles with water absorption below 0.5 %.

