

RIALTO 45x45 / 60x60 / 30x60 / 20x60



Properties

- Size** 45x45 / 60x60 / 30x60 / 20x60
- Shape** Square, Rectangle
- Surface** Matt
- Colours** Beige
- Texture** Stone, Mosaic
- Character** Rectified, Porcelain, Frost resistance, Mosaic on the net
- Category** Wall tiles, Floor tiles, Stone & Concrete, Mosaics



RIT008 30x60 cm
Thickness 8.5
Package contains 1.44 m², 8



RIT005 45x45 cm
Thickness 9
Package contains 1.42 m², 7




RIT002 60x60 cm
Thickness 10
Package contains 1.44 m², 4



RIT004 33x33 cm
Thickness 9
Package contains 1 m²



RIT006 20x60 cm
Thickness 9
Package contains 1.44 m², 12



RIT007 20x60 cm
Thickness 9
Package contains 1.44 m², 12

Explanations

MT **Matte surface**
Matt glaze tile.

RT **Rectified tiles**
Rectified tiles are also known as dimensionally stable tiles. These are tiles that have been mechanically trimmed to a certain size after they have been fired so that their edges are 90°. Achieved uniform size, consistency and optimum precision give the tile a cleaner finish and fewer deviations between tiles. Rektifizierte Fliesen sind für Verlegung mit einer Mindestfuge von 2 mm geeignet.

PO**Porcelain tiles**

By pushing into the mold under high pressure remains in the ceramics minimum of air bubbles. It is then fired at high temperatures, making the final product hard, strong and abrasion resistant. At the same time, it is less absorbent. Located universal use in interior and exterior, on walls and floors. Sintered paving is especially suited to high-stressed areas such as tiles or building facades.

**Frost resistance**

Frost resistance is determined by the degree of water absorption of the tile (ie it does not provide water to freeze it). For tiles for indoor use is not required frost resistance and moisture absorption is usually more than 10 %. In contrast, frost-resistant glazed tiles have an absorption of up to 3 %. For exterior are suitable sintered tiles with water absorption below 0.5 %.

**Mosaic**

The mosaic consists of small-dimensional elements whose edge length does not usually exceed 100 mm. Their connection - gluing on a suitable substrate (e.g. fabric or bond "Joint-point" system), a mosaic is formed on the network. This makes it easier to work with it: a hobby or scissors is sufficient to divide. Mosaic on the net is an excellent choice for tiling rounded places. Also suitable for wall and shower tiles. It may be glass, stone or ceramic.