

BODO 20x60 / 30x60 / 33,3x90 / 45x45 / 60x60 / 60x120



Properties

Size	20x60 / 30x60 / 33,3x90 / 45x45 / 60x60 / 60x120
Shape	Square, Rectangle
Surface	Matt, Gloss
Colours	White, Beige, Brown, Gray
Texture	Marble
Character	Rectified, Porcelain, Frost resistance, Anti-slip surface
Category	Wall tiles, Floor tiles, Stone & Concrete

MT

BR

RT


PO



BOD028 30x60 cm
Thickness 8.7
Package contains 1.26 m², 7

PEI
IV


BOD013 45x45 cm
Thickness 8.5
Package contains 1.42 m², 7

PEI
IV


BOD014 45x45 cm
Thickness 8.5
Package contains 1.42 m², 7

PEI
IV



BOD015 45x45 cm
Thickness 8.5
Package contains 1.42 m², 7

PEI
IV


BOD016 45x45 cm
Thickness 8.5
Package contains 1.42 m², 7

PEI
IV


BOD017 60x120 cm
Thickness 10
Package contains 1.428 m², 2


PEI
IV


BOD018 60x120 cm
Thickness 10
Package contains 1.428 m², 2

PEI
IV


BOD019 60x120 cm
Thickness 10
Package contains 1.428 m², 2


PEI
IV



BOD020 60x120 cm
Thickness 10
Package contains 1.428 m², 2




BOD021 60x60 cm
Thickness 9.5
Package contains 1.41 m², 4




BOD022 60x60 cm
Thickness 9.5
Package contains 1.41 m², 4



BOD023 60x60 cm
Thickness 9.5
Package contains 1.41 m², 4




BOD024 60x60 cm
Thickness 9.5
Package contains 1.41 m², 4



BOD025 30x60 cm
Thickness 8.7
Package contains 1.26 m², 7



BOD026 30x60 cm
Thickness 8.7
Package contains 1.26 m², 7



BOD027 30x60 cm
Thickness 8.7
Package contains 1.26 m², 7




BOD002 33,3x90 cm
Thickness 10.5
Package contains 1.1988 m², 4




BOD004 33,3x90 cm
Thickness 10.5
Package contains 1.1988 m², 4



BOD032 20x60 cm
Thickness 9
Package contains 1.56 m², 13




BOD006 33,3x90 cm
Thickness 10.5
Package contains 1.1988 m², 4




BOD033 20x60 cm
Thickness 9
Package contains 1.56 m², 13



BOD034 20x60 cm
Thickness 9
Package contains 1.56 m², 13



BOD008 33,3x90 cm
Thickness 10.5
Package contains 1.1988 m², 4



BOD035 20x60 cm
Thickness 9
Package contains 1.56 m², 13

Explanations

MT

Matte surface
Matt glaze tile.

BR

Glossy surface
Glossy glaze tile.

RT

Rectified tiles
Rectified tiles are also known as dimensionally stable tiles. These are tiles that have been mechanically trimmed to a certain size after they have been fired so that their edges are 90°. Achieved uniform size, consistency and optimum precision give the tile a cleaner finish and fewer deviations between tiles. Rektifizierte Fliesen sind für Verlegung mit einer Mindestfuge von 2 mm geeignet.

PO

Porcelain tiles
By pushing into the mold under high pressure remains in the ceramics minimum of air bubbles. It is then fired at high temperatures, making the final product hard, strong and abrasion resistant. At the same time, it is less absorbent. Located universal use in interior and exterior, on walls and floors. Sintered paving is especially suited to high-stressed areas such as tiles or building facades.



Frost resistance
Frost resistance is determined by the degree of water absorption of the tile (ie it does not provide water to freeze it). For tiles for indoor use is not required frost resistance and moisture absorption is usually more than 10 %. In contrast, frost-resistant glazed tiles have an absorption of up to 3 %. For exterior are suitable sintered tiles with water absorption below 0.5 %.



Anti-slip surface
Non-slip tiles meet prescribed friction coefficient values. This indicates the resistance of the pavement in shear friction. Anti-slip tiles provide greater safety in areas where there is an increased risk of slipping, whether walking barefoot or in footwear.

